

GLACIER MILLWORKS

WOOD SIDING TOUCH-UP INSTRUCTIONS

OVERVIEW

This document provides guidance for touching up exterior wood siding using the stain sealer supplied by Glacier Millworks. Proper preparation and application will ensure a long-lasting and aesthetically pleasing finish.

MATERIALS NEEDED

- Stain sealer (corresponding color to the siding)
- Clean, lint-free cloths
- Soap and water solution
- Clean brush or applicator

PREPARATION

01 Inspect the Siding:

- Carefully examine every piece of siding for cut ends, dings, scratches, and cracks prior to installation.
- Identify any large cracks or severely damaged sections that require removal prior to installation.

02 Touch-Up Areas:

- Any siding with cut ends must be sealed before installation.
- Use the stain sealer that corresponds to the color of the siding being treated.
- For pieces with dings, scratches, or cracks, ensure these areas are also touched up and sealed prior to installation.

APPLICATION PROCESS

01 Clean the Surface:

- Ensure the surfaces to be sealed are free from dirt, dust, and debris.

02 Apply Stain Sealer:

- Mix Sealer well prior to each use.
- Using a clean brush or applicator, apply the stain sealer to the identified areas.
- Ensure even coverage and blend the touch-up areas with the surrounding siding.

FINAL NOTES

- Ensure that the stain sealer does not freeze during the application process. Store and apply in a temperature-controlled environment to maintain product efficacy.
- Clean any tools and applicators with soap and water immediately after use to prevent hardening of the stain sealer.

By following these instructions, you will help ensure that the exterior wood siding not only looks great but also maintains its integrity and durability. For any further questions, please contact Glacier Millworks customer service.



GLACIER MILLWORKS

583 N Complex Dr
Kalispell, Montana 59901
GlacierMillworks.com